



COMPOSTING EQUIPMENT

EMDEK EFB CHOPPER/APPLICATOR



MODEL	7 CBM EFB CHOPPER	9 CBM EFB CHOPPER
Hopper Capacity	7 CBM	9 CBM
Max. Load Approx., kg	Approx. 2,450kg depending on the type and density of material used.	Approx. 3,150kg depending on the type and density of material used.
Type Of Hopper	Mild Steel	
Shape Of Hopper	Square Shape	
Effective Discharge	Single side on the left hand side. Hydraulically operated discharge chains	
Chopping System	Twin augers fitted with 80pcs heavy duty blades & counter blades. The auger design is such that it is able to mix the material evenly while it is being chopped.	
Discharging System	Discharge conveyor size (1200 mm L x 900 mm W)	
PTO Speed (max.), rpm	540	
Tractor PTO	Suitable for tractor PTO shafts with 6 splines 1 3/8" diameter.	
Tractor HP Required, HP	75 (min)	90 (min)
Construction Material Used	Hopper and chassis are of heavy gauge mild steel.	
Gearbox	Heavy duty planetary coupler gearbox with reduction gearbox.	
Clutch & PTO	Heavy duty PTO shaft with appropriate torque limiter protection mechanism.	
Axle & Wheels	8 ton axle with 265/70 R19.5 tyres	10 ton axle with 265/70 R19.5 tyres

