



SPRAYING EQUIPMENT

EMDEK TRACTOR MOUNTED SPRAYER



BLANKET BOOM



MODEL	200	400	600	800
Tank Capacity, L	200	400	600	800
Tank Material	Fiberglass	Strong Polyethylene (PE) with UV Protection		
Spraying Hose Diameter, Length & Qty.	0.85 cm x 50 m x 2 pcs			
Suction hose dia. & length	3.2 cm x 5 m			
Spraying productivity, ha/day	15 - 20			
Pump Pressure, bar	AR70 pump: 20 bar AR30 pump : 40 bar			
Tractor horsepower Require, HP	25-50	30-50	55-95	55-95
Max Tractor PTO, RPM	540			
PTO Drive Shaft	T10 Drive Shaft			
Tractor Linkage Category	Cat I		Cat I & II	
Dimension, cm (L x W x H)	130 x 114 x 119	135 x 147 x 140	142 x 155 x 158	145 x 175 x 165
Weight, kg	± 168	± 209	± 256	± 276
Optional Spray Boom & Nozzle	4 m (8 nozzles)	4 m (8 nozzles) 6 m (12 nozzles) 8 m (16 nozzles)	10 m (20 nozzles) 12 m (24 nozzles)	

FRAME TYPES FOR TRACTOR MOUNTED SPRAYER

TANK TYPES FOR TRACTOR MOUNTED SPRAYER



STANDARD MODEL

Steel frame primed with zinc chromate and top coated with quality enamel paint



GALVANIZED MODEL

Steel frame with hot dipped zinc galvanized against rust



Fiberglass Tank



Polyethylene (PE) Tank