



# OTHER EQUIPMENT

## EMDEK FLOATING PUMP



**F5.5HP-G**




**F15HP-G**

MODEL		F5.5HP-G	F15HP-G
PUMP	Type of Centrifugal	Single Stage	
	Suction Dia., mm	Ø 65	Ø 80
	Outlet Dia., mm	Ø 65	
	Max. Flow, L/min	600 at 0.2 MPa	1,140 at 0.2 MPa
	Normal Nozzle size, mm	Ø 19 / Ø 22	
	Max. head,m	45	60
ENGINE	Type	Vertical, Single-Cylinder, Recoil Start, Air-Cooled, 4-Stroke	
	Output Power	5.5 HP (HONDA)	15 HP (LONCIN)
	RPM	3,600	
	Fuel Tank, L	2.5	4
	Lubrication	Oil Lubrication	
	Ignition	Wheel Magneto	
	Starting System	Recoil	Electric, Recoil, Remote
	Engine Oil Capacity,L	0.6	0.9
	Fuel Consumption,L/h	1.5	3.5
OTHERS	Dimensions, cm	69.0 x 55.0 x 45.0	83.0 x 77.0 x 49.0
	Weight, kg	± 26	± 58

## ACCESSORIES INCLUDED



Suction Hose c/w Coupling  
(for 13HP-G and 27HP-G)



Suction Filter  
(for 13HP-G and 27HP-G)



Spray Hose  
c/w Coupling



Spray Nozzle



Tools & Parts



Remote Control  
(for F15HP-G model)



Battery Charger  
(for F15HP-G model)