



# LIVESTOCK EQUIPMENT

## EMDEK FEED MIXER / TMR



MODEL	5 CBM TMR FEED MIXER	7 CBM TMR FEED MIXER	9 CBM TMR FEED MIXER
Hopper Capacity, CBM	5	7	9
Max. Load Approx., kg	Approx. 1,750kg depending on the type and density of material used.	Approx. 2,450kg depending on the type and density of material used.	Approx. 3,150kg depending on the type and density of material used.
Type Of Hopper	Mild Steel		
Shape Of Hopper	Square Shape		
Effective Discharge	Single side on the left hand side. Hydraulically operated discharge chains		
Chopping System	Twin augers fitted with heavy duty blades & counter blades. The auger design is such that it is able to mix the material evenly while it is being chopper.		
Discharging System	Discharge conveyor size (1200mm L x 900mm W)		
PTO Speed (max.), rpm	540		
Tractor PTO	Suitable for tractor PTO shafts with 6 splines 1 3/8" diameter.		
Tractor HP Required, HP	60 - 95	70 - 95	90 - 95
Construction Material Used	Hopper and chassis are of heavy gauge mild steel.		
Gearbox	Heavy duty planetary coupler gearbox with reduction gearbox.		
Clutch & PTO	Heavy duty PTO shaft with appropriate torque limiter protection mechanism.		
Axle & Wheels	6 ton axle with 265/70 R19.5 tyres	8 ton axle with 265/70 R19.5 tyres	10 ton axle with 265/70 R19.5 tyres