




GRASS CUTTING EQUIPMENT

EMDEK RANGE OF ROTARY SLASHER



MD SERIES MODEL

Medium Duty
Rotary Slasher



HD SERIES MODEL

Heavy Duty
Rotary Slasher



HF SERIES MODEL

Heavy Frame
Rotary Slasher

MODEL	MEDIUM DUTY ROTARY SLASHER			HEAVY DUTY ROTARY SLASHER		HEAVY FRAME ROTARY SLASHER	
	MD36	MD48	MD60	HD60	HD70	HF60	HF70
Cutting width, cm	90	120	150	150	180	150	180
Tractor HP required, HP	20 - 45	25 - 45	45 - 55	55 - 95			
Tractor Linkage Category	Cat I & II						
PTO Drive Shaft	T40			T60			
	with shearbolt clutch			with safety slip clutch			
Max. Tractor PTO, RPM	540						
Blades	Twin Blades (8mm thick crank type)			Twin Blades (12mm thick crank type)		Twin Blades (12mm thick step - down type)	
Body	3 mm thick steel sheet reinforced front/ rear			4 mm thick steel sheet reinforced front/ rear		4.5 mm thick steel sheet reinforced front/ rear	
Headstock	Flatbar					Heavy Duty Tubular	
Weight, kg	± 120	± 170	± 270	± 370	± 400	± 380	± 440

STANDARD EQUIPMENT

OPTIONAL FEATURES



Cast iron gearbox with
hardened gears and shaft



Heavy duty blades
and beam




PTO drive shaft with
safety slip clutch



Twin Skids for height
adjustment



Hot Dipped Galvanized body,
skids and headstock



Front and rear roller kit